

NAME

mxwldmn - filter rays based upon their weight

PARAMETERS

mxwldmn uses the standard parameter interface

input *file*

Input ray stream. If the filename is the string `stdin`, it reads the UNIX standard input stream. It accepts rays in **bpipe** format.

output *file*

Output ray stream. If the filename is the string `stdout`, it writes to the UNIX standard output stream. It writes rays in **bpipe** format.

seed1 *unsigned int*

The first seed for the random number generator.

seed2 *unsigned int*

The second seed for the random number generator.

block *unsigned int*

The block in the random number sequence at which to start using random numbers. (There are 1,048,576 blocks of 1,073,741,824 random numbers each).

version *boolean*

Print out **mxwldmn**'s version and exit.

help *boolean*

Print out help and exit.

debug *list*

A list of debug flags. None are presently defined.

DESCRIPTION

mxwldmn reads a ray stream in **bpipe** format and discards rays based upon their weight. It generates a uniformly distributed random number (using **ranlib**'s **genunf** function) between 0 and 1, and discards the ray if its weight is less than the random number. The weights of rays which are not discarded are set to unity; their polarization information is discarded as well.

It writes out a **bpipe** formatted ray stream.

COPYRIGHT & LICENSE

Copyright 2006 Smithsonian Astrophysical Observatory

This software is released under the GNU General Public License. You may find a copy at

<http://www.fsf.org/copyleft/gpl.html>

AUTHOR

Diab Jerius <djerius@cfa.harvard.edu>