

AH`HELP` for CIAO 3.4

`_NARGS`

Context: [slangrtl](#)*Jump to:* [Description](#) [Example](#) [See Also](#)

Synopsis

The number of parameters passed to a function

Syntax

```
Integer_Type _NARGS
```

Description

The value of the `_NARGS` variable represents the number of arguments passed to the function. This variable is local to each function.

Example

This example uses the `_NARGS` variable to print the list of values passed to the function:

```
define print_values ()
{
  variable arg;

  if (_NARGS == 0)
  {
    message ("Nothing to print");
    return;
  }
  foreach (__pop_args (_NARGS))
  {
    arg = ();
    vmessage ("Argument value is: %S", arg.value);
  }
}
```

See Also

slangrtl

[class id](#), [class type](#), [eqs](#), [get reference](#), [is initialized](#), [pop args](#), [push args](#), [nargs](#), [typeof](#), [array info](#), [dup](#), [is defined](#), [is struct type](#), [length](#), [typecast](#), [typeof](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/_NARGS.tm.html
Last modified: December 2006