



AHELP for CIAO 3.4

fdopen

Context: [slangrtl](#)*Jump to:* [Description](#) [See Also](#)

Synopsis

Convert a FD_Type file descriptor to a stdio File_Type object

Syntax

```
File_Type fdopen (FD_Type, String_Type mode)
```

Description

The fdopen function creates and returns a stdio File_Type object from the open FD_Type descriptor fd. The mode parameter corresponds to the mode parameter of the fopen function and must be consistent with the mode of the descriptor fd. The function returns NULL upon failure and sets errno.

The fclose function does not close the File_Type object returned from this function. The underlying file object must be closed by the close function.

See Also

slangrtl

[clearerr](#), [close](#), [dup_fd](#), [fclose](#), [feof](#), [ferror](#), [fflush](#), [fgets](#), [fgetslines](#), [fileno](#), [fopen](#), [fputs](#), [fread](#), [fseek](#), [ftell](#), [fwrite](#), [isatty](#), [lseek](#), [mkdir](#), [open](#), [pclose](#), [popen](#), [read](#), [write](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/fdopen.tm.html>
Last modified: December 2006

