



AHELP for CIAO 3.4

paramclose

Context: [paramio](#)

Jump to: [Description](#) [Example](#) [See Also](#)

Synopsis

Close a parameter file opened by paramopen.

Syntax

```
paramclose( Param_File_Type )
```

Description

Close the parameter file associated with the given Param_File_Type variable – the return value of paramopen().

As with all the paramio routines, the PF_Errno variable is set to 0 on success, or on error it is set to one of the error codes listed in the paramio documentation.

Example

```
variable fp = paramopen("dmextract");
% use fp in other paramio routines
paramclose(fp);
```

Here we open the parameter file for dmextract and then close it. In real-world applications you would use one of the other paramio routines to query or change the parameter file in between opening and closing it.

See Also

concept

[parameter](#)

modules

[paramio](#)

paramio

[paccess](#), [paramopen](#), [pget](#), [pgets](#), [plist_names](#), [pquery](#), [pset](#), [punlearn](#)

tools

[dmhistory](#), [dmkeypar](#), [dmmakepar](#), [dmreadpar](#), [paccess](#), [pdump](#), [pget](#), [pline](#), [plist](#), [pquery](#), [pset](#), [punlearn](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/paramclose.html>
Last modified: December 2006