



AHELP for CIAO 3.4

regExtent

Context: [region](#)

Jump to: [Description](#) [Example](#) [CHANGES IN CIAO 3.2](#) [Bugs](#) [See Also](#)

Synopsis

Calculate the bounding box of a region.

Syntax

```
(xmin, ymin, xmax, ymax) = regExtent( Region_Type Region )
```

where xmin, ymin, xmax, and ymax are all Double_Type

Description

The regExtent routine returns the bounding box of a region. It is primarily useful if you wish to use the six-argument form of regArea().

Example

```
chips> require("region")
chips> reg = regParse("circle(10,10,4)-rect(4,2,5,4)")
chips> (x0,y0,x1,y1) = regExtent( reg )
chips> vmessage( "Bounding box is (%.1f,%.1f) to (%.1f,%.1f)", x0, y0,
x1, y1 )
Bounding box is (6.0,6.0) to (14.0,14.0)
```

CHANGES IN CIAO 3.2

This function is new to CIAO 3.2.

Bugs

See the [bugs page for the region library](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

modules

[region](#)

region

regExtent

Ahelp: regExtent – CIAO 3.4

[regarea](#), [regextent](#), [reginsideregion](#), [regparse](#), [regprintregion](#), [regregionstring](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/regextent.html>
Last modified: December 2006