



 AHELP for CIAO 3.4

set_par

Context: [sherpa](#)

Jump to: [Description](#) [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Module function for setting model parameter values, etc.

Syntax

```
Integer_Type set_par(Struct_Type)
Integer_Type set_par(String_Type,String_Type,{Float_Type | String_Type})

Success/Error Return Values: 1/0

Arguments:

(1) A parameter information structure

or

(1) The parameter name
(2) The field to set
(3) The new value for that field
```

Description

The first form of this function assumes as input the parameter information structure output by `get_par`, e.g.

```
sherpa> GAUSS[g]
sherpa> foo = get_par("g.pos")
sherpa> print(foo)
name           = g.pos
model          = gauss1d
type          = src
value         = 0
min           = -3.40282e+38
max           = 3.40282e+38
delta         = -1
units         = NULL
frozen        = 0
linked        = 0
linkexpr      = NULL
```

The second form of this function takes the arguments listed above; fields to set include:

Allowed set_par Arguments

Argument	Description
value	the parameter value (either a number, or a string filename)
min	the current (soft) lower bound on allowed parameter values
max	the current (soft) upper bound on allowed parameter values
delta	the initial step size for the parameter in fits (or -1 to use the default step size)
frozen	if 1, freeze the parameter's value; if 0, thaw it
thawed	if 1, thaw the parameter's value; if 0, freeze it

See the Sherpa command CREATE for more information.

Example 1

Get a parameter structure; change two fields; set back into Sherpa:

```

sherpa> GAUSS[g]
sherpa> foo = get_par("g.pos")
sherpa> print(foo)
name           = g.pos
model          = gauss1d
type           = src
value          = 0
min            = -3.40282e+38
max            = 3.40282e+38
delta          = -1
units          = NULL
frozen         = 0
linked         = 0
linkexpr       = NULL
sherpa> foo.value = 15.5
sherpa> foo.min = 0.0
sherpa> () = set_par(foo)
sherpa> SHOW g
gauss1d[g] (integrate: on)
  Param  Type      Value      Min      Max      Units
  -----
  1  fwhm  thawed      10  1.1755e-38  3.4028e+38
  2   pos  thawed     15.5      0  3.4028e+38
  3  ampl  thawed      1 -3.403e+38  3.4028e+38
    
```

Example 2

Change two parameter attributes directly:

```

sherpa> GAUSS[g]
sherpa> () = set_par("g.pos", "value", 15.5)
sherpa> () = set_par("g.pos", "min", 0.0)
sherpa> SHOW g
gauss1d[g] (integrate: on)
  Param  Type      Value      Min      Max      Units
  -----
  1  fwhm  thawed      10  1.1755e-38  3.4028e+38
  2   pos  thawed     15.5      0  3.4028e+38
  3  ampl  thawed      1 -3.403e+38  3.4028e+38
    
```

Bugs

See the [Sherpa bug pages](#) online for an up-to-date listing of known bugs.

See Also

sherpa

[autoest](#), [background](#), [create](#), [create_model](#), [createparamset](#), [fit](#), [freeze](#), [get_defined_models](#),
[get_model_params](#), [get_models](#), [get_num_par](#), [get_par](#), [get_stackexpr](#), [getx](#), [gety](#), [guess](#), [instrument](#),
[integrate](#), [is_paramset](#), [jointmode](#), [kernel](#), [lineid](#), [linkparam](#), [mdl](#), [modeexpr](#), [modelstack](#),
[nestedmodel](#), [noise](#), [paramprompt](#), [paramset](#), [pileup](#), [rename](#), [run_fit](#), [set_paramset](#), [set_stackexpr](#),
[source](#), [thaw](#), [truncate](#), [unlink](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian
Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
http://cxc.harvard.edu/ciao3.4/set_par.html
Last modified: December 2006

