



---

*AHELP for CIAO 3.4*

## writeascii

Context: [varmm](#)*Jump to:* [Description](#) [Examples](#) [Bugs](#) [See Also](#)

---

## Synopsis

S-Lang function to create an ASCII output file from S-Lang arrays

## Syntax

```
writeascii( filename, col1 )
writeascii( filename, col1, col2 )
writeascii( filename, col1, col2, ..., colN )
```

## Description

Write the supplied S-lang arrays (i.e. "col1", "col2", ...) to an ASCII file. To write to stdout (i.e. the screen) or stderr use a filename of "stdout" or "stderr" respectively, without the quotes.

## Example 1

Here we create two columns, and then write them to an ASCII file called foo.dat.

```
chips> x = [1:10];
chips> y = sin(x) + 0.5 * x;
chips> writeascii("foo.dat",x,y);
```

As the output is an ASCII file, it can be accessed using standard UNIX tools, such as cat:

```
unix% cat foo.dat
1      1.34147
2      1.9093
3      1.64112
4      1.2432
5      1.54108
6      2.72058
7      4.15699
8      4.98936
9      4.91212
10     4.45598
```

## Example 2

Instead of writing to a file, we can use `writeascii()` to write to the screen (ie `stdout`). This can also be achieved using the `"printarr()"` `Varmm` function, although it is limited to printing out only one array. This example also shows how you can access a field within a `S-Lang` structure, here the second column read from the file `"foo.dat"`.

```
chips> foo = readfile("foo.dat")
chips> writeascii(stdout,foo.col2)
1.34147
1.9093
1.64112
1.2432
1.54108
2.72058
4.15699
4.98936
4.91212
4.45598
```

## Example 3

The default format used to print out the column data may not match your needs; for instance it may not display enough significant figures. The format used can be changed by calling the `set_float_format()` function from the `S-Lang Run-Time Library`. In the following example we change the format to use the format `%13.6e`, which means to use exponential notation with 6 numbers after the decimal point and placed within a space 13 characters wide.

```
chips> a = [0:10:2] / 3.0
chips> b = 10^a
chips> writeascii( stdout, a, b )
0      1
0.666667      4.64159
1.333333 21.5443
2      100
2.666667 464.159
3.333333 2154.43
chips> set_float_format( "%13.6e" )
chips> writeascii( stdout, a, b )
0.000000e+00      1.000000e+00
6.666667e-01      4.641589e+00
1.333333e+00      2.154435e+01
2.000000e+00      1.000000e+02
2.666667e+00      4.641589e+02
3.333333e+00      2.154435e+03
chips> set_float_format( "%g" )
```

Note that all the columns are printed using this format and that we reset the format to the default value (`"%g"`) to avoid changing the layout of other commands, such as `print()` and `printarr()`.

## Bugs

See the [bugs page for the Varmm library](#) on the CIAO website for an up-to-date listing of known bugs.

## See Also

*modules*

[varmm](#)

*varmm*

## Ahelp: writeascii – CIAO 3.4

[fits](#), [bitpix](#), [readarf](#), [readascii](#), [readbintab](#), [readfile](#), [readimage](#), [readpha](#), [readrdb](#), [readrmf](#), [writefits](#)

---

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.  
60 Garden Street, Cambridge, MA 02138 USA.  
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:  
<http://cxc.harvard.edu/ciao3.4/writeascii.html>  
Last modified: December 2006

Ahelp: writeascii – CIAO 3.4